



# Polyurea Stone Sealer Part - A

## Infinity Innovative Coatings Ltd

Part Number: **Not Available**

Version No: **1.2**

Safety Data Sheet (Conforms to Annex II of REACH (1907/2006) - Regulation 2020/878)

Issue Date: **02/02/2023**

Print Date: **02/02/2023**

L.REACH.GBR.EN

### SECTION 1 Identification of the substance / mixture and of the company / undertaking

#### 1.1. Product Identifier

Product name	Polyurea Stone Sealer Part - A
Synonyms	Not Available
Other means of identification	Not Available

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Not Available
Uses advised against	Not Applicable

#### 1.3. Details of the manufacturer or supplier of the safety data sheet

Registered company name	Infinity Innovative Coatings Ltd
Address	42 Drumalig Road Carryduff Belfast BT88EQ United Kingdom
Telephone	02890136728
Fax	Not Available
Website	Not Available
Email	info@infinity-effects.com

#### 1.4. Emergency telephone number

Association / Organisation	NHS
Emergency telephone numbers	018092166
Other emergency telephone numbers	Not Available


### SECTION 2 Hazards identification

#### 2.1. Classification of the substance or mixture

Classification according to regulation (EC) No 1272/2008 [CLP] and amendments [1]	H319 - Serious Eye Damage/Eye Irritation Category 2, H317 - Sensitisation (Skin) Category 1, H412 - Hazardous to the Aquatic Environment Long-Term Hazard Category 3
Legend:	1. Classification by vendor; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

#### 2.2. Label elements

**Polyurea Stone Sealer**

<b>Hazard pictogram(s)</b>	
----------------------------	---

<b>Signal word</b>	<b>Warning</b>
--------------------	----------------

**Hazard statement(s)**

<b>H319</b>	Causes serious eye irritation.
<b>H317</b>	May cause an allergic skin reaction.
<b>H412</b>	Harmful to aquatic life with long lasting effects.

**Supplementary statement(s)**

Not Applicable

**Precautionary statement(s) Prevention**

<b>P280</b>	Wear protective gloves, protective clothing, eye protection and face protection.
<b>P261</b>	Avoid breathing mist/vapours/spray.
<b>P273</b>	Avoid release to the environment.
<b>P264</b>	Wash all exposed external body areas thoroughly after handling.
<b>P272</b>	Contaminated work clothing should not be allowed out of the workplace.

**Precautionary statement(s) Response**

<b>P302+P352</b>	IF ON SKIN: Wash with plenty of water.
<b>P305+P351+P338</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
<b>P333+P313</b>	If skin irritation or rash occurs: Get medical advice/attention.
<b>P337+P313</b>	If eye irritation persists: Get medical advice/attention.
<b>P362+P364</b>	Take off contaminated clothing and wash it before reuse.

**Precautionary statement(s) Storage**

Not Applicable

**Precautionary statement(s) Disposal**

<b>P501</b>	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
-------------	--

**2.3. Other hazards**

REACH - Art.57-59: The mixture does not contain Substances of Very High Concern (SVHC) at the SDS print date.

**SECTION 3 Composition / information on ingredients**

**3.1. Substances**

See 'Composition on ingredients' in Section 3.2

**3.2. Mixtures**

1.CAS No 2.EC No 3.Index No 4.REACH No	%[weight]	Name	Classification according to regulation (EC) No 1272/2008 [CLP] and amendments	SCL / M-Factor	Nanoform Particle Characteristics
1.136210-32-7 2.412-060-9 3.607-350-00-9 4.Not Available	40-50	<u>aspartic acid</u> , <u>N,N'-(methylenedicyclohexanediy)bis-.ester</u>	Sensitisation (Skin) Category 1, Hazardous to the Aquatic Environment Long-Term Hazard Category 3; H317, H412 [2]	Not Available	Not Available
1.136210-30-5 2.429-270-1 3.607-521-00-8 4.Not Available	10-20	<u>aspartic acid</u> , <u>N,N'-(methylenedicyclohexanediy)bis-.ester</u>	Sensitisation (Skin) Category 1, Hazardous to the Aquatic Environment Long-Term Hazard	Not Available	Not Available

Continued...

1.CAS No 2.EC No 3.Index No 4.REACH No	%[weight]	Name	Classification according to regulation (EC) No 1272/2008 [CLP] and amendments	SCL / M-Factor	Nanoform Particle Characteristics
			Category 3; H317, H412 [2]		
1.108-32-7 2.203-572-1 3.607-194-00-1 4.Not Available	20	<u>propylene carbonate</u>	Serious Eye Damage/Eye Irritation Category 2; H319 [2]	Not Available	Not Available
<b>Legend:</b>		1. Classification by vendor; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from C&L; * EU IOELVs available; [e] Substance identified as having endocrine disrupting properties			

## SECTION 4 First aid measures

### 4.1. Description of first aid measures

<b>Eye Contact</b>	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> <li>▶ Wash out immediately with fresh running water.</li> <li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>▶ Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
<b>Skin Contact</b>	<p>If skin contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Immediately remove all contaminated clothing, including footwear.</li> <li>▶ Flush skin and hair with running water (and soap if available).</li> <li>▶ Seek medical attention in event of irritation.</li> </ul>
<b>Inhalation</b>	<ul style="list-style-type: none"> <li>▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>▶ Other measures are usually unnecessary.</li> </ul>
<b>Ingestion</b>	<ul style="list-style-type: none"> <li>▶ <b>If swallowed do NOT induce vomiting.</b></li> <li>▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>▶ Observe the patient carefully.</li> <li>▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>▶ Seek medical advice.</li> <li>▶ If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.</li> </ul>

### 4.2 Most important symptoms and effects, both acute and delayed

See Section 11

### 4.3. Indication of any immediate medical attention and special treatment needed

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours. Treat symptomatically.

As in all cases of suspected poisoning, follow the ABCDEs of emergency medicine (airway, breathing, circulation, disability, exposure), then the ABCDEs of toxicology (antidotes, basics, change absorption, change distribution, change elimination).

For poisons (where specific treatment regime is absent):

#### BASIC TREATMENT

- ▶ Establish a patent airway with suction where necessary.
- ▶ Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- ▶ Administer oxygen by non-rebreather mask at 10 to 15 L/min.
- ▶ Monitor and treat, where necessary, for pulmonary oedema.
- ▶ Monitor and treat, where necessary, for shock.
- ▶ Anticipate seizures.
- ▶ **DO NOT** use emetics. Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.

#### ADVANCED TREATMENT

- ▶ Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- ▶ Positive-pressure ventilation using a bag-valve mask might be of use.

Continued...

**Polyurea Stone Sealer**

- ▶ Monitor and treat, where necessary, for arrhythmias.
- ▶ Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- ▶ Drug therapy should be considered for pulmonary oedema.
- ▶ Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- ▶ Treat seizures with diazepam.
- ▶ Proparacaine hydrochloride should be used to assist eye irrigation.

BRONSTEIN, A.C. and CURRANCE, P.L.

EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

**SECTION 5 Firefighting measures**

**5.1. Extinguishing media**

- ▶ Foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.
- ▶ Water spray or fog - Large fires only.

**5.2. Special hazards arising from the substrate or mixture**

<b>Fire Incompatibility</b>	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
-----------------------------	--

**5.3. Advice for firefighters**

<b>Fire Fighting</b>	<ul style="list-style-type: none"> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ Wear breathing apparatus plus protective gloves.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water courses.</li> <li>▶ Use water delivered as a fine spray to control fire and cool adjacent area.</li> <li>▶ <b>DO NOT</b> approach containers suspected to be hot.</li> <li>▶ Cool fire exposed containers with water spray from a protected location.</li> <li>▶ If safe to do so, remove containers from path of fire.</li> <li>▶ Equipment should be thoroughly decontaminated after use.</li> </ul>
<b>Fire/Explosion Hazard</b>	<p>Combustible. Will burn if ignited. Combustion products include: carbon monoxide (CO) carbon dioxide (CO2) aldehydes nitrogen oxides (NOx) other pyrolysis products typical of burning organic material. May emit poisonous fumes. May emit corrosive fumes. <b>WARNING:</b> Long standing in contact with air and light may result in the formation of potentially explosive peroxides.</p>

**SECTION 6 Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

See section 8

**6.2. Environmental precautions**

See section 12

**6.3. Methods and material for containment and cleaning up**

<b>Minor Spills</b>	<ul style="list-style-type: none"> <li>▶ Clean up all spills immediately.</li> <li>▶ Avoid contact with skin and eyes.</li> <li>▶ Wear impervious gloves and safety goggles.</li> <li>▶ Trowel up/scrape up.</li> <li>▶ Place spilled material in clean, dry, sealed container.</li> <li>▶ Flush spill area with water.</li> </ul>
<b>Major Spills</b>	<ul style="list-style-type: none"> <li>▶ Clear area of personnel and move upwind.</li> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ Wear breathing apparatus plus protective gloves.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> <li>▶ Stop leak if safe to do so.</li> </ul>

- ▶ Contain spill with sand, earth or vermiculite.
- ▶ Collect recoverable product into labelled containers for recycling.
- ▶ Neutralise/decontaminate residue (see Section 13 for specific agent).
- ▶ Collect solid residues and seal in labelled drums for disposal.
- ▶ Wash area and prevent runoff into drains.
- ▶ After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.
- ▶ If contamination of drains or waterways occurs, advise emergency services.

#### 6.4. Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

### SECTION 7 Handling and storage

#### 7.1. Precautions for safe handling

<b>Safe handling</b>	<p>The substance accumulates peroxides which may become hazardous only if it evaporates or is distilled or otherwise treated to concentrate the peroxides. The substance may concentrate around the container opening for example. Purchases of peroxidisable chemicals should be restricted to ensure that the chemical is used completely before it can become peroxidised.</p> <ul style="list-style-type: none"> <li>▶ A responsible person should maintain an inventory of peroxidisable chemicals or annotate the general chemical inventory to indicate which chemicals are subject to peroxidation. An expiration date should be determined. The chemical should either be treated to remove peroxides or disposed of before this date.</li> <li>▶ The person or laboratory receiving the chemical should record a receipt date on the bottle. The individual opening the container should add an opening date.</li> <li>▶ Unopened containers received from the supplier should be safe to store for 18 months.</li> <li>▶ Opened containers should not be stored for more than 12 months.</li> <li>▶ Avoid all personal contact, including inhalation.</li> <li>▶ Wear protective clothing when risk of exposure occurs.</li> <li>▶ Use in a well-ventilated area.</li> <li>▶ Prevent concentration in hollows and sumps.</li> <li>▶ <b>DO NOT enter confined spaces until atmosphere has been checked.</b></li> <li>▶ <b>DO NOT allow material to contact humans, exposed food or food utensils.</b></li> <li>▶ Avoid contact with incompatible materials.</li> <li>▶ <b>When handling, DO NOT eat, drink or smoke.</b></li> <li>▶ Keep containers securely sealed when not in use.</li> <li>▶ Avoid physical damage to containers.</li> <li>▶ Always wash hands with soap and water after handling.</li> <li>▶ Work clothes should be laundered separately. Launder contaminated clothing before re-use.</li> <li>▶ Use good occupational work practice.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.</li> </ul>
<b>Fire and explosion protection</b>	See section 5
<b>Other information</b>	<p>Consider storage under inert gas.</p> <ul style="list-style-type: none"> <li>▶ Store in original containers.</li> <li>▶ Keep containers securely sealed.</li> <li>▶ Store in a cool, dry, well-ventilated area.</li> <li>▶ Store away from incompatible materials and foodstuff containers.</li> <li>▶ Protect containers against physical damage and check regularly for leaks.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> </ul>

#### 7.2. Conditions for safe storage, including any incompatibilities

<b>Suitable container</b>	<ul style="list-style-type: none"> <li>▶ Metal can or drum</li> <li>▶ Packaging as recommended by manufacturer.</li> <li>▶ Check all containers are clearly labelled and free from leaks.</li> </ul>
<b>Storage incompatibility</b>	<ul style="list-style-type: none"> <li>▶ Segregate from alcohol, water.</li> <li>▶ The unhindered oxygen atom found on cyclic ethers such as the epoxides, oxetanes, furans, dioxanes and pyrans, carries two unshared pairs of electrons - a structure which favors the formation of coordination complexes and the solvation of cations.</li> <li>▶ Cyclic ethers are used as important solvents, as chemical intermediate and as monomers for ring-opening polymerization.</li> <li>▶ They are unstable at room temperature due to possibility of peroxide formation; stabiliser is sometimes needed for storage and transportation.</li> </ul> <p>NOTE: Ethers lacking non-methyl hydrogen atoms adjacent to the ether link are thought to be relatively safe</p> <ul style="list-style-type: none"> <li>▶ Avoid reaction with oxidising agents</li> </ul>

<b>Hazard categories in accordance with Regulation (EC) No 1272/2008</b>	Not Available
<b>Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of</b>	Not Available



X — Must not be stored together

O — May be stored together with specific preventions

+ — May be stored together

Note: Depending on other risk factors, compatibility assessment based on the table above may not be relevant to storage situations, particularly where large volumes of dangerous goods are stored and handled. Reference should be made to the Safety Data Sheets for each substance or article and risks assessed accordingly.

### 7.3. Specific end use(s)

See section 1.2

## SECTION 8 Exposure controls / personal protection

### 8.1. Control parameters

Ingredient	DNELs Exposure Pattern Worker	PNECs Compartment
aspartic acid, N,N'-(methylenedicyclohexanediyl)bis-,ester	Dermal 11.9 mg/kg bw/day (Systemic, Chronic) Inhalation 84 mg/m <sup>3</sup> (Systemic, Chronic) Inhalation 672 mg/m <sup>3</sup> (Systemic, Acute) Dermal 4.2 mg/kg bw/day (Systemic, Chronic) * Inhalation 14.5 mg/m <sup>3</sup> (Systemic, Chronic) * Oral 4.2 mg/kg bw/day (Systemic, Chronic) * Dermal 4.2 mg/kg bw/day (Systemic, Acute) * Inhalation 14.5 mg/m <sup>3</sup> (Systemic, Acute) * Oral 4.2 mg/kg bw/day (Systemic, Acute) *	0 mg/L (Water (Fresh)) 0 mg/L (Water - Intermittent release) 0.21 mg/kg sediment dw (Sediment (Fresh Water)) 0.02 mg/kg sediment dw (Sediment (Marine)) 0.1 mg/kg soil dw (Soil) 31.1 mg/L (STP)
aspartic acid, N,N'-(methylenedicyclohexanediyl)bis-,ester	Dermal 4 mg/kg bw/day (Systemic, Chronic) Inhalation 28 mg/m <sup>3</sup> (Systemic, Chronic) Inhalation 112 mg/m <sup>3</sup> (Systemic, Acute) Dermal 1.4 mg/kg bw/day (Systemic, Chronic) * Inhalation 4.8 mg/m <sup>3</sup> (Systemic, Chronic) * Oral 1.4 mg/kg bw/day (Systemic, Chronic) * Dermal 1.4 mg/kg bw/day (Systemic, Acute) * Inhalation 4.8 mg/m <sup>3</sup> (Systemic, Acute) * Oral 1.4 mg/kg bw/day (Systemic, Acute) *	0 mg/L (Water (Fresh)) 0 mg/L (Water - Intermittent release) 0.21 mg/kg sediment dw (Sediment (Fresh Water)) 0.02 mg/kg sediment dw (Sediment (Marine)) 0.1 mg/kg soil dw (Soil) 31.1 mg/L (STP)
propylene carbonate	Dermal 20 mg/kg bw/day (Systemic, Chronic) Inhalation 70.53 mg/m <sup>3</sup> (Systemic, Chronic) Dermal 10 mg/cm <sup>2</sup> (Local, Chronic) Inhalation 20 mg/m <sup>3</sup> (Local, Chronic) Dermal 10 mg/kg bw/day (Systemic, Chronic) * Inhalation 17.4 mg/m <sup>3</sup> (Systemic, Chronic) * Oral 10 mg/kg bw/day (Systemic, Chronic) * Inhalation 10 mg/m <sup>3</sup> (Local, Chronic) *	0.9 mg/L (Water (Fresh)) 0.09 mg/L (Water - Intermittent release) 9 mg/L (Water (Marine)) 0.81 mg/kg soil dw (Soil) 7400 mg/L (STP)

\* Values for General Population

### Occupational Exposure Limits (OEL)

#### INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Not Available	Not Available	Not Available	Not Available	Not Available	Not Available	Not Available

Not Applicable

### Emergency Limits

Continued...

Ingredient	TEEL-1	TEEL-2	TEEL-3
propylene carbonate	34 mg/m3	370 mg/m3	2,200 mg/m3

Ingredient	Original IDLH	Revised IDLH
aspartic acid, N,N'-(methylenedicyclohexanediyl)bis-,ester	Not Available	Not Available
aspartic acid, N,N'-(methylenedicyclohexanediyl)bis-,ester	Not Available	Not Available
propylene carbonate	Not Available	Not Available

**Occupational Exposure Banding**

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
aspartic acid, N,N'-(methylenedicyclohexanediyl)bis-,ester	D	> 0.1 to ≤ 1 ppm
aspartic acid, N,N'-(methylenedicyclohexanediyl)bis-,ester	D	> 0.1 to ≤ 1 ppm
propylene carbonate	E	≤ 0.1 ppm

**Notes:**

*Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.*

**MATERIAL DATA**

Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations. Present day expectations require that nearly every individual should be protected against even minor sensory irritation and exposure standards are established using uncertainty factors or safety factors of 5 to 10 or more. On occasion animal no-observable-effect-levels (NOEL) are used to determine these limits where human results are unavailable. An additional approach, typically used by the TLV committee (USA) in determining respiratory standards for this group of chemicals, has been to assign ceiling values (TLV C) to rapidly acting irritants and to assign short-term exposure limits (TLV STELs) when the weight of evidence from irritation, bioaccumulation and other endpoints combine to warrant such a limit. In contrast the MAK Commission (Germany) uses a five-category system based on intensive odour, local irritation, and elimination half-life. However this system is being replaced to be consistent with the European Union (EU) Scientific Committee for Occupational Exposure Limits (SCOEL); this is more closely allied to that of the USA.

OSHA (USA) concluded that exposure to sensory irritants can:

- ▶ cause inflammation
- ▶ cause increased susceptibility to other irritants and infectious agents
- ▶ lead to permanent injury or dysfunction
- ▶ permit greater absorption of hazardous substances and
- ▶ acclimate the worker to the irritant warning properties of these substances thus increasing the risk of overexposure.

Tenth Annual Report on Carcinogens: Substance anticipated to be Carcinogen

[National Toxicology Program: U.S. Dep. of Health & Human Services 2002]

Exposed individuals are **NOT** reasonably expected to be warned, by smell, that the Exposure Standard is being exceeded.

Odour Safety Factor (OSF) is determined to fall into either Class C, D or E.

The Odour Safety Factor (OSF) is defined as:

OSF= Exposure Standard (TWA) ppm/ Odour Threshold Value (OTV) ppm

Classification into classes follows:

Class	OSF	Description
A	550	Over 90% of exposed individuals are aware by smell that the Exposure Standard (TLV-TWA for example) is being reached, even when distracted by working activities
B	26-550	As "A" for 50-90% of persons being distracted
C	1-26	As "A" for less than 50% of persons being distracted
D	0.18-1	10-50% of persons aware of being tested perceive by smell that the Exposure Standard is being reached
E	<0.18	As "D" for less than 10% of persons aware of being tested

**8.2. Exposure controls****8.2.1. Appropriate engineering controls**

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if

designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure.

Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection.

An approved self contained breathing apparatus (SCBA) may be required in some situations.

Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25-0.5 m/s (50-100 f/min.)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

### 8.2.2. Personal protection



### Eye and face protection

- ▶ Safety glasses with side shields.
- ▶ Chemical goggles.
- ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]

### Skin protection

See Hand protection below

### Hands/feet protection

- ▶ Wear chemical protective gloves, e.g. PVC.
- ▶ Wear safety footwear or safety gumboots, e.g. Rubber

#### NOTE:

- ▶ The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
- ▶ Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

### Body protection

See Other protection below

### Other protection

- ▶ Overalls.
- ▶ P.V.C apron.
- ▶ Barrier cream.
- ▶ Skin cleansing cream.
- ▶ Eye wash unit.



Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Required minimum protection factor	Maximum gas/vapour concentration present in air p.p.m. (by volume)	Half-face Respirator	Full-Face Respirator
up to 10	1000	A-AUS / Class1 P2	-
up to 50	1000	-	A-AUS / Class 1 P2
up to 50	5000	Airline *	-
up to 100	5000	-	A-2 P2
up to 100	10000	-	A-3 P2
100+			Airline**

\* - Continuous Flow \*\* - Continuous-flow or positive pressure demand

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO<sub>2</sub>), G = Agricultural chemicals, K = Ammonia(NH<sub>3</sub>), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

### 8.2.3. Environmental exposure controls

See section 12

## SECTION 9 Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Moisture sensitive. Family of products which vary in their physical properties as a result of variations in production. Data presented here is for typical family member.		
<b>Physical state</b>	Gel	<b>Relative density (Water = 1)</b>	Not Available
<b>Odour</b>	Not Available	<b>Partition coefficient n-octanol / water</b>	Not Available
<b>Odour threshold</b>	Not Available	<b>Auto-ignition temperature (°C)</b>	Not Available
<b>pH (as supplied)</b>	Not Available	<b>Decomposition temperature (°C)</b>	Not Available
<b>Melting point / freezing point (°C)</b>	Not Available	<b>Viscosity (cSt)</b>	Not Available
<b>Initial boiling point and boiling range (°C)</b>	Not Available	<b>Molecular weight (g/mol)</b>	Not Available
<b>Flash point (°C)</b>	Not Available	<b>Taste</b>	Not Available
<b>Evaporation rate</b>	Not Available	<b>Explosive properties</b>	Not Available
<b>Flammability</b>	Not Available	<b>Oxidising properties</b>	Not Available
<b>Upper Explosive Limit (%)</b>	Not Available	<b>Surface Tension (dyn/cm or mN/m)</b>	Not Available
<b>Lower Explosive Limit (%)</b>	Not Available	<b>Volatile Component (%vol)</b>	Not Available
<b>Vapour pressure (kPa)</b>	Not Available	<b>Gas group</b>	Not Available
<b>Solubility in water</b>	Not Available	<b>pH as a solution (1%)</b>	Not Available
<b>Vapour density (Air = 1)</b>	Not Available	<b>VOC g/L</b>	Not Available
<b>Nanoform Solubility</b>	Not Available	<b>Nanoform Particle Characteristics</b>	Not Available
<b>Particle Size</b>	Not Available		

### 9.2. Other information

Not Available

**SECTION 10 Stability and reactivity**

<b>10.1.Reactivity</b>	See section 7.2
<b>10.2. Chemical stability</b>	Product is considered stable and hazardous polymerisation will not occur.
<b>10.3. Possibility of hazardous reactions</b>	See section 7.2
<b>10.4. Conditions to avoid</b>	See section 7.2
<b>10.5. Incompatible materials</b>	See section 7.2
<b>10.6. Hazardous decomposition products</b>	See section 5.3

**SECTION 11 Toxicological information****11.1. Information on toxicological effects**

<b>Inhaled</b>	The material is not thought to produce either adverse health effects or irritation of the respiratory tract following inhalation (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
<b>Ingestion</b>	Accidental ingestion of the material may be damaging to the health of the individual. High molecular weight material; on single acute exposure would be expected to pass through gastrointestinal tract with little change / absorption. Occasionally accumulation of the solid material within the alimentary tract may result in formation of a bezoar (concretion), producing discomfort. Swallowing of the liquid may cause aspiration of vomit into the lungs with the risk of haemorrhaging, pulmonary oedema, progressing to chemical pneumonitis; serious consequences may result. Signs and symptoms of chemical (aspiration) pneumonitis may include coughing, gasping, choking, burning of the mouth, difficult breathing, and bluish coloured skin (cyanosis).
<b>Skin Contact</b>	Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.  Limited evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
<b>Eye</b>	Evidence exists, or practical experience predicts, that the material may cause eye irritation in a substantial number of individuals and/or may produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals. Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.
<b>Chronic</b>	On the basis, primarily, of animal experiments, concern has been expressed that the material may produce carcinogenic or mutagenic effects; in respect of the available information, however, there presently exists inadequate data for making a satisfactory assessment. Practical experience shows that skin contact with the material is capable either of inducing a sensitisation reaction in a substantial number of individuals, and/or of producing a positive response in experimental animals. Substances that can cause occupational asthma (also known as asthmagens and respiratory sensitisers) can induce a state of specific airway hyper-responsiveness via an immunological, irritant or other mechanism. Once the airways have become hyper-responsive, further exposure to the substance, sometimes even to tiny quantities, may cause respiratory symptoms. These symptoms can range in severity from a runny nose to asthma. Not all workers who are exposed to a sensitiser will become hyper-responsive and it is impossible to identify in advance who are likely to become hyper-responsive. Substances that can cause occupational asthma should be distinguished from substances which may trigger the symptoms of asthma in people with pre-existing air-way hyper-responsiveness. The latter substances are not classified as asthmagens or respiratory sensitisers Wherever it is reasonably practicable, exposure to substances that can cause occupational asthma should be prevented. Where this is not possible the primary aim is to apply adequate standards of control to prevent workers from becoming hyper-

Continued...

responsive.

Activities giving rise to short-term peak concentrations should receive particular attention when risk management is being considered. Health surveillance is appropriate for all employees exposed or liable to be exposed to a substance which may cause occupational asthma and there should be appropriate consultation with an occupational health professional over the degree of risk and level of surveillance.

Cyclic ethers, including tetrahydrofuran, furan and 1,4-dioxane, produce neoplasms and carcinomas in experimental animals, typically of the liver; other target organs include the adrenal gland, nasal cavity and gall-bladder. 1,4-Dioxane was a promoter in a two-stage skin carcinogenic study in mice. Results of studies with cyclic ethers indicate that carcinogenicity is often species and sex dependent. Furan has been used to induce apoptosis (programmed cell death). Oxetanes are under investigation.

Polyurea Stone Sealer	TOXICITY	IRRITATION
	Not Available	Not Available
aspartic acid, N,N'-(methylenedicyclohexanediyl)bis-,ester	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg <sup>[2]</sup>	Eye : Mild
	Inhalation(Rat) LC50: >4.224 mg/L4h <sup>[1]</sup>	Skin : Moderate
	Oral (Rat) LD50: >2000 mg/kg <sup>[2]</sup>	
aspartic acid, N,N'-(methylenedicyclohexanediyl)bis-,ester	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg <sup>[2]</sup>	Eye : Mild
	Inhalation(Rat) LC50: >4.224 mg/L4h <sup>[1]</sup>	Skin : Moderate
	Oral (Rat) LD50: >2000 mg/kg <sup>[2]</sup>	
propylene carbonate	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >=2000 mg/kg <sup>[1]</sup>	Eye (rabbit): 60 mg - moderate
	Oral (Rat) LD50: >5000 mg/kg <sup>[2]</sup>	Eye: adverse effect observed (irritating) <sup>[1]</sup>
		Skin (human): 100 mg/3d-I moderate
		Skin (rabbit): 500 mg moderate
		Skin: no adverse effect observed (not irritating) <sup>[1]</sup>

**Legend:**

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

<b>ASPARTIC ACID, N,N'-(METHYLENEDICYCLOHEXANEDIYL)BIS-,ESTER</b>	for similar substance CAS 136210-10-32-7: Exogenous allergic alveolitis is induced essentially by allergen specific immune-complexes of the IgG type; cell-mediated reactions (T lymphocytes) may be involved. Such allergy is of the delayed type with onset up to four hours following exposure.
<b>PROPYLENE CARBONATE</b>	<p><b>WARNING:</b> This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans.</p> <p>The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.</p> <p>The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.</p> <p>for propylene carbonate: Numerous adequate and reliable acute toxicity tests are available on propylene carbonate. Oral and dermal tests meet OECD and EPA test guidelines. Propylene carbonate is practically nontoxic following acute exposures; the oral LD50 is &gt;.5000 mg/kg and the dermal LD50 is &gt;3000 mg/kg. No further testing is recommended.</p> <p>Subchronic studies (13- 14 weeks) of propylene carbonate by inhalation (aerosol) and oral (gavage) routes were conducted in rats according to current guidelines. The oral study indicated low systemic toxicity from propylene carbonate (NOAEL = 5000 mg/kg/day). In the inhalation study, no systemic toxicity was seen at concentrations up to 1000 mg/m<sup>3</sup>; however, there was periocular irritation and swelling in a few males at 500 and 1000 mg/m<sup>3</sup>. A dermal carcinogenicity study in mice did not indicate tumorigenic potential or systemic toxicity from 2 years of exposure to propylene carbonate. No further testing is recommended.</p> <p>There is a negative Ames in vitro mutagenicity assay of propylene carbonate. A single intraperitoneal injection of 1666 mg/kg propylene carbonate did not induce an increase in micronuclei when examined after 30,48 and 72 hours. The mutagenicity battery is satisfactorily filled; no further mutagenicity testing is recommended.</p> <p>Gavage administration of propylene carbonate to pregnant rats days 6-15 of gestation resulted in systemic toxicity at doses of 3000 and 5000 mg/kg/day, including mortality (not seen in 13 week</p>

**Polyurea Stone Sealer**

	<p>study of non-pregnant rats). The NOAEL for maternal toxicity was 1000 mg/kg/day. This indicates that pregnant rats are more susceptible to propylene carbonate than are non-pregnant rats. There were no significant differences in live litter size, average fetal weight, percentage of males, or malformed fetuses.</p> <p>No studies of the effect of propylene carbonate on reproduction are available. However, no adverse effects on testis, ovaries, or accessory sex organs were noted in rats following oral or inhalation of propylene carbonate for 13 weeks. Therefore, reproductive effects from propylene carbonate are unlikely</p>
<p><b>Polyurea Stone Sealer &amp; ASPARTIC ACID, N,N'-(METHYLENEDICYCLOHEXANEDIYL)BIS-,ESTER</b></p>	<p>The following information refers to contact allergens as a group and may not be specific to this product.</p> <p>Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.</p>
<p><b>ASPARTIC ACID, N,N'-(METHYLENEDICYCLOHEXANEDIYL)BIS-,ESTER</b></p>	<p>Evidence of sensitisation (adjuvant test) * After the first challenge very mild to clearly visible skin reddening was observed in 85% of the test substance animals. After the second challenge, very mild to clearly visible skin reddening was observed in 50% and 35% of the test substance animals challenged with 25% and 12% test substance respectively. A scaly administration site was observed in some animals. Rat repeat dose oral toxicity - 29 days NOAEL 1000 mg/kg/day * Genotoxicity ? bacterial reverse mutation non mutagenic * Genotoxicity ? in vitro not determined * Genotoxicity ? in vivo erythrocyte micronucleus test non clastogenic * The notified chemical is considered to be of low acute toxicity via the oral, dermal and inhalation routes. Irritation and Sensitisation. The material is considered to be a slight skin and eye irritant and mild respiratory irritant and a skin sensitiser. As skin reactions were observed in 85% of animals at a concentration of 50%, the substance is considered to be a strong sensitiser. The potential for respiratory sensitisation cannot be ruled out. Repeated Dose Toxicity. In a 28 day study in rats, the No Observed Adverse Effect Level (NOAEL) was established as 1000 mg/kg bw/day based on the absence of adverse treatment related effects. Mutagenicity. The material was negative in an Ames test and an in vivo erythrocyte micronucleus test. The substance is not considered to be mutagenic. Neurotoxicity: In the in vivo mouse erythrocyte micronucleus test, following intraperitoneal administration of a fairly high dose (5345 mg/kg bw) some evidence of non-specific neurological impairment was seen. However, this was not observed in any of the tests conducted on any other species and could either be species-specific or an expression of generalised toxicity induced at high doses, as opposed to specific neurotoxicity. * NICNAS Report</p> <p>Allergic reactions which develop in the respiratory passages as bronchial asthma or rhinoconjunctivitis, are mostly the result of reactions of the allergen with specific antibodies of the IgE class and belong in their reaction rates to the manifestation of the immediate type. In addition to the allergen-specific potential for causing respiratory sensitisation, the amount of the allergen, the exposure period and the genetically determined disposition of the exposed person are likely to be decisive. Factors which increase the sensitivity of the mucosa may play a role in predisposing a person to allergy. They may be genetically determined or acquired, for example, during infections or exposure to irritant substances. Immunologically the low molecular weight substances become complete allergens in the organism either by binding to peptides or proteins (haptens) or after metabolism (prohaptens).</p> <p>Particular attention is drawn to so-called atopic diathesis which is characterised by an increased susceptibility to allergic rhinitis, allergic bronchial asthma and atopic eczema (neurodermatitis) which is associated with increased IgE synthesis.</p>

Acute Toxicity	✘	Carcinogenicity	✘
Skin Irritation/Corrosion	✘	Reproductivity	✘
Serious Eye Damage/Irritation	✔	STOT - Single Exposure	✘
Respiratory or Skin sensitisation	✔	STOT - Repeated Exposure	✘
Mutagenicity	✘	Aspiration Hazard	✘

**Legend:** ✘ – Data either not available or does not fill the criteria for classification  
 ✔ – Data available to make classification

**11.2 Information on other hazards****11.2.1. Endocrine Disruption Properties**

Not Available

**11.2.2. Other Information**

Continued...

See Section 11.1

**SECTION 12 Ecological information****12.1. Toxicity**

Polyurea Stone Sealer	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available

aspartic acid, N,N'-(methylenedicyclohexanediyl)bis-,ester	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96h	Fish	66mg/l	2
	EC50	72h	Algae or other aquatic plants	34mg/l	2
	EC50	48h	Crustacea	88.6mg/l	Not Available
	NOEC(ECx)	48h	Crustacea	10mg/l	Not Available

aspartic acid, N,N'-(methylenedicyclohexanediyl)bis-,ester	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96h	Fish	66mg/l	2
	EC50	72h	Algae or other aquatic plants	34mg/l	2
	EC50	48h	Crustacea	88.6mg/l	Not Available
	NOEC(ECx)	48h	Crustacea	10mg/l	Not Available

propylene carbonate	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96h	Fish	1000mg/l	1
	EC50	72h	Algae or other aquatic plants	>900mg/l	1
	EC50	48h	Crustacea	>1000mg/l	1
	NOEC(ECx)	72h	Algae or other aquatic plants	900mg/l	1

**Legend:** *Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data*

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

For high molecular weight synthetic polymers: (according to the Sustainable Futures (SF) program (U.S. EPA 2005b; U.S. EPA 2012c) polymer assessment guidance.)

High MW polymers are expected:

- to have low vapour pressure and are not expected to undergo volatilization .
- to adsorb strongly to soil and sediment
- to be non-biodegradable (not anticipated to be assimilated by microorganisms.- therefore, biodegradation is not expected to be an important removal process.

However many exceptions exist

High MW polymers are not expected to undergo removal by other degradative processes under environmental conditions for propylene carbonate:

**Environmental fate:**

Data on the transport of propylene carbonate between environmental compartments has been estimated using EPIWIN; propylene carbonate will partition mostly to water and soil;1% to air; 46% to water; 53% to soil.

Does not absorb UV and therefore is unlikely to be photodegradable.

**Biodegradation:** OECD Test Guideline 301B (Modified Sturm Test)

Propylene carbonate was readily biodegradable by activated domestic sludge under aerobic conditions. More than 85% degraded after 29 days

**Ecotoxicity**

Invertebrate EC50: >1000 mg/l

Aquatic plant EC50: >=929 mg/l

Acute toxicity studies on fish and daphnia on a propylene carbonate analog, butylene carbonate, were conducted according to OECD Guidelines, following GLP guidelines. Butylene carbonate (CAS # 4437-85-8) is considered an acceptable surrogate for propylene carbonate because of similar physical-chemical properties. In rainbow trout the LC50 for butylene carbonate was 480 mg/l and in Daphnia the EC50 was >1000 mg/l. Based on similarity to butylene carbonate, propylene carbonate is not expected to be significantly more toxic to aquatic organisms. The low toxicity of butylene carbonate provides adequate information to conclude that propylene carbonate is not likely to be more than slightly toxic to aquatic organisms.

**Toxicity to Aquatic plants** (e.g., Algae): OECD Test Guideline 201 Propylene carbonate did not affect cell density, area under the growth curve, or growth rate of unicellular green alga, *Selenastrum capricornutum*, after 72 and 96 hours of exposure at levels up to 929 mg/l, measured concentration.

Continued...

**Polyurea Stone Sealer**

**Biodegradation:** OECD Test Guideline 301B (Modified Sturm Test)

Propylene carbonate was readily biodegradable by activated domestic sludge under aerobic conditions. More than 85% degraded after 29 days.

**DO NOT discharge into sewer or waterways.**

**12.2. Persistence and degradability**

Ingredient	Persistence: Water/Soil	Persistence: Air
propylene carbonate	HIGH	HIGH

**12.3. Bioaccumulative potential**

Ingredient	Bioaccumulation
propylene carbonate	LOW (LogKOW = -0.41)

**12.4. Mobility in soil**

Ingredient	Mobility
propylene carbonate	LOW (KOC = 14.85)

**12.5. Results of PBT and vPvB assessment**

	P	B	T
Relevant available data	Not Available	Not Available	Not Available
PBT	✗	✗	✗
vPvB	✗	✗	✗
PBT Criteria fulfilled?	No		
vPvB	No		

**12.6. Endocrine Disruption Properties**

Not Available

**12.7. Other adverse effects**

Not Available

**SECTION 13 Disposal considerations**

**13.1. Waste treatment methods**

<b>Product / Packaging disposal</b>	<ul style="list-style-type: none"> <li>▸ Containers may still present a chemical hazard/ danger when empty.</li> <li>▸ Return to supplier for reuse/ recycling if possible.</li> </ul> <p>Otherwise:</p> <ul style="list-style-type: none"> <li>▸ If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.</li> <li>▸ Where possible retain label warnings and SDS and observe all notices pertaining to the product.</li> <li>▸ <b>DO NOT allow wash water from cleaning or process equipment to enter drains.</b></li> <li>▸ It may be necessary to collect all wash water for treatment before disposal.</li> <li>▸ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li> <li>▸ Where in doubt contact the responsible authority.</li> <li>▸ Recycle wherever possible or consult manufacturer for recycling options.</li> <li>▸ Consult State Land Waste Authority for disposal.</li> <li>▸ Bury or incinerate residue at an approved site.</li> <li>▸ Recycle containers if possible, or dispose of in an authorised landfill.</li> </ul>
<b>Waste treatment options</b>	Not Available
<b>Sewage disposal options</b>	Not Available

**SECTION 14 Transport information**

**Labels Required**

<b>Marine Pollutant</b>	NO
<b>HAZCHEM</b>	Not Applicable

**Land transport (ADR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

14.1. UN number	Not Applicable	
14.2. UN proper shipping name	Not Applicable	
14.3. Transport hazard class(es)	Class	Not Applicable
	Subrisk	Not Applicable
14.4. Packing group	Not Applicable	
14.5. Environmental hazard	Not Applicable	
14.6. Special precautions for user	Hazard identification (Kemler)	Not Applicable
	Classification code	Not Applicable
	Hazard Label	Not Applicable
	Special provisions	Not Applicable
	Limited quantity	Not Applicable
	Tunnel Restriction Code	Not Applicable

**Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

14.1. UN number	Not Applicable	
14.2. UN proper shipping name	Not Applicable	
14.3. Transport hazard class(es)	ICAO/IATA Class	Not Applicable
	ICAO / IATA Subrisk	Not Applicable
	ERG Code	Not Applicable
14.4. Packing group	Not Applicable	
14.5. Environmental hazard	Not Applicable	
14.6. Special precautions for user	Special provisions	Not Applicable
	Cargo Only Packing Instructions	Not Applicable
	Cargo Only Maximum Qty / Pack	Not Applicable
	Passenger and Cargo Packing Instructions	Not Applicable
	Passenger and Cargo Maximum Qty / Pack	Not Applicable
	Passenger and Cargo Limited Quantity Packing Instructions	Not Applicable
	Passenger and Cargo Limited Maximum Qty / Pack	Not Applicable

**Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

14.1. UN number	Not Applicable	
14.2. UN proper shipping name	Not Applicable	
14.3. Transport hazard class(es)	IMDG Class	Not Applicable
	IMDG Subrisk	Not Applicable
14.4. Packing group	Not Applicable	
14.5. Environmental hazard	Not Applicable	
14.6. Special precautions for user	EMS Number	Not Applicable
	Special provisions	Not Applicable
	Limited Quantities	Not Applicable

**Inland waterways transport (ADN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

14.1. UN number	Not Applicable
-----------------	----------------

14.2. <b>UN proper shipping name</b>	Not Applicable	
14.3. <b>Transport hazard class(es)</b>	Not Applicable	Not Applicable
14.4. <b>Packing group</b>	Not Applicable	
14.5. <b>Environmental hazard</b>	Not Applicable	
14.6. <b>Special precautions for user</b>	Classification code	Not Applicable
	Special provisions	Not Applicable
	Limited quantity	Not Applicable
	Equipment required	Not Applicable
	Fire cones number	Not Applicable

**14.7. Transport in bulk according to Annex II of MARPOL and the IBC code**

Not Applicable

**14.8. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code**

Product name	Group
aspartic acid, N,N'-(methylenedicyclohexanediyl)bis-,ester	Not Available
aspartic acid, N,N'-(methylenedicyclohexanediyl)bis-,ester	Not Available
propylene carbonate	Not Available

**14.9. Transport in bulk in accordance with the ICG Code**

Product name	Ship Type
aspartic acid, N,N'-(methylenedicyclohexanediyl)bis-,ester	Not Available
aspartic acid, N,N'-(methylenedicyclohexanediyl)bis-,ester	Not Available
propylene carbonate	Not Available

**SECTION 15 Regulatory information****15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture****aspartic acid, N,N'-(methylenedicyclohexanediyl)bis-,ester is found on the following regulatory lists**

Europe EC Inventory

European Union (EU) Regulation (EC) No 1272/2008 on Classification, Labelling and Packaging of Substances and Mixtures - Annex VI

**aspartic acid, N,N'-(methylenedicyclohexanediyl)bis-,ester is found on the following regulatory lists**

Europe EC Inventory

European Union (EU) Regulation (EC) No 1272/2008 on Classification, Labelling and Packaging of Substances and Mixtures - Annex VI

**propylene carbonate is found on the following regulatory lists**

Europe EC Inventory

European Union - European Inventory of Existing Commercial Chemical Substances (EINECS)

European Union (EU) Regulation (EC) No 1272/2008 on Classification, Labelling and Packaging of Substances and Mixtures - Annex VI

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable - : Directives 98/24/EC, - 92/85/EEC, - 94/33/EC, - 2008/98/EC, - 2010/75/EU; Commission Regulation (EU) 2020/878; Regulation (EC) No 1272/2008 as updated through ATPs.

**Information according to 2012/18/EU (Seveso III):**

<b>Seveso Category</b>	Not Available
------------------------	---------------

**15.2. Chemical safety assessment**

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

**ECHA SUMMARY**



Ingredient	CAS number	Index No	ECHA Dossier
aspartic acid, N,N'-(methylenedicyclohexanediyl)bis-,ester	136210-32-7	607-350-00-9	Not Available

Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)	Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Skin Sens. 1; Aquatic Chronic 3	GHS07; Wng	H317; H412
2	Skin Sens. 1B; Aquatic Chronic 1	GHS07; Wng; GHS09	H317; H410

Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.

Ingredient	CAS number	Index No	ECHA Dossier
aspartic acid, N,N'-(methylenedicyclohexanediyl)bis-,ester	136210-30-5	607-521-00-8	Not Available

Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)	Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Skin Sens. 1; Aquatic Chronic 3	GHS07; Wng	H317; H412
2	Skin Sens. 1B; Aquatic Chronic 1	GHS07; Wng; GHS09	H317; H410

Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.

Ingredient	CAS number	Index No	ECHA Dossier
propylene carbonate	108-32-7	607-194-00-1	Not Available

Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)	Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Eye Irrit. 2	GHS07; Wng	H319
2	Eye Irrit. 2A; Skin Irrit. 2; Acute Tox. 4	GHS07; Wng	H319; H315; H312
1	Skin Irrit. 2; Eye Irrit. 2; STOT SE 3	GHS07; Wng	H315; H319; H335
2	Skin Irrit. 2; Eye Irrit. 2; STOT SE 3	GHS07; Wng	H315; H319; H335
1	Skin Irrit. 2; Eye Irrit. 2; STOT SE 3	GHS07; Wng	H315; H319; H335
2	Skin Irrit. 2; Eye Irrit. 2; STOT SE 3	GHS07; Wng	H315; H319; H335

Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.

## National Inventory Status

National Inventory	Status
Australia - AIIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (aspartic acid, N,N'-(methylenedicyclohexanediyl)bis-,ester; aspartic acid, N,N'-(methylenedicyclohexanediyl)bis-,ester; propylene carbonate)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	No (aspartic acid, N,N'-(methylenedicyclohexanediyl)bis-,ester)
Japan - ENCS	No (aspartic acid, N,N'-(methylenedicyclohexanediyl)bis-,ester; aspartic acid, N,N'-(methylenedicyclohexanediyl)bis-,ester)
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	No (aspartic acid, N,N'-(methylenedicyclohexanediyl)bis-,ester; aspartic acid, N,N'-(methylenedicyclohexanediyl)bis-,ester)
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	No (aspartic acid, N,N'-(methylenedicyclohexanediyl)bis-,ester; aspartic acid, N,N'-(methylenedicyclohexanediyl)bis-,ester)
Vietnam - NCI	Yes
Russia - FBEPH	Yes
<b>Legend:</b>	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

**SECTION 16 Other information**

<b>Revision Date</b>	02/02/2023
<b>Initial Date</b>	03/02/2023

**Full text Risk and Hazard codes**

<b>H312</b>	Harmful in contact with skin.
<b>H315</b>	Causes skin irritation.
<b>H335</b>	May cause respiratory irritation.
<b>H410</b>	Very toxic to aquatic life with long lasting effects.

**Other information****Ingredients with multiple cas numbers**

<b>Name</b>	<b>CAS No</b>
aspartic acid, N,N'-(methylenedicyclohexanediy)bis-,ester	136210-32-7, 188364-76-3
propylene carbonate	108-32-7, 51260-39-0, 16606-55-6

Classification of the preparation and its individual components has drawn on official and authoritative sources using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection

EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro-organisms

EN 13832 Footwear protecting against chemicals

EN 133 Respiratory protective devices

**Definitions and abbreviations**

PC—TWA: Permissible Concentration-Time Weighted Average

PC—STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit.

IDLH: Immediately Dangerous to Life or Health Concentrations

ES: Exposure Standard

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index

AIIC: Australian Inventory of Industrial Chemicals

DSL: Domestic Substances List

NDSL: Non-Domestic Substances List

IECSC: Inventory of Existing Chemical Substance in China

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

NLP: No-Longer Polymers

ENCS: Existing and New Chemical Substances Inventory

KECI: Korea Existing Chemicals Inventory

NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act

TCSI: Taiwan Chemical Substance Inventory

INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

**Polyurea Stone Sealer**

**Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]**

<b>Classification according to regulation (EC) No 1272/2008 [CLP] and amendments</b>	<b>Classification Procedure</b>
Serious Eye Damage/Eye Irritation Category 2, H319	Calculation method
Sensitisation (Skin) Category 1, H317	Calculation method
Hazardous to the Aquatic Environment Long-Term Hazard Category 3, H412	Calculation method